

Key safe

Model "SUHL", VdS class I



Illustration: Article 13404

Insurance protection based on break-in test according to VdS 2450/EN 1143-1 class I, private up to 65,000 € commercially up to 20,000 € (in case of professional and appropriate anchoring according to the enclosed instructions). Certified and quality-surveyed by the VdS Certification Body in Cologne.

Body in multi-wall design.

Multi-wall door of 105 mm thickness.

The multi-wall design assures a defined break-in protection against attacks with mechanically and thermally acting burglary tools (burglary protection 30/50 RU).

Serial design prepared for floor anchoring.

The partition walls running on high-precision telescopic extension rails are fully extendable.

Plastic hook rails, height-adjustable by means of a 14-mm-grid system.

Interchangeable display.

Lateral hook distance: 30 mm

Hook length: 18 mm

Locking by means of double bit lock of lock class I (incl. 2 keys).

Upon request also available with mechanic number combination lock or electronic lock.

Colour: RAL 7035 grey

Article	Model	Outer dimensions in mm HxWxD	Key hooks Number	Partition walls Number	Hook rails Number	Weight kg
13400	SUHL	600x500x500	300	4	30	132
13401	SUHL	800x500x500	420	4	42	170
13402	SUHL	600x650x550	500	6	50	168
13403	SUHL	800x650x550	700	6	70	180
13404	SUHL	800x700x550	840	7	84	190
13405	SUHL	1000x700x550	1200	7	120	240
13406	SUHL	1200x700x550	1560	7	156	280
13407	SUHL	1500x700x550	2040	7	204	390
13408	SUHL	1500x780x550	2380	8	238	405
13409	SUHL	1200x850x550	2080	9	208	310
13410	SUHL	1500x850x550	2720	9	272	420
13411	SUHL	1800x850x550	3360	9	336	500
13412	SUHL 2 pd.	1800x1200x550	5040	13	504	720
13220	Mechanical number combination lock instead of double bit lock					
13221	Electronic lock with revision instead of double bit lock					
13222	Electronic lock without revision instead of double bit lock					