

Safety door

Model "HELGOLAND T", VdS class III



Illustration: Article 95603 with electronic lock, aluminium fitting as well as with locking and blocking barrier

Insurance protection:

The amounts insured have to be agreed upon with the property insurer.

Heavy design according to the VdS guidelines 2450 / EN 1143-1 class III.

Multi-walled door with an overall door thickness of 120 mm.

Locking by means of a double bit security lock, lock class II (incl. 2 keys).

Four-sided bolt locking system, standard frame 240 mm.

An additional installation of a locking and blocking barrier to be operated from inside is possible.

Upon request also with mechanical number combination lock or electronic lock available.

Special designs available upon request.

Colour: RAL 7035 grey

Article	Model	Outer dimensions in mm H x W x T	Door passage in mm H x W	weight kg
95600	HELGOLANDT	1500 x 700 x 240	1393 x 576	600
95601	HELGOLANDT	1700 x 900 x 240	1593 x 776	700
95602	HELGOLANDT	1850 x 900 x 240	1745 x 776	720
95603	HELGOLANDT	2000 x 1000 x 240	1893 x 876	830
60620	Mechanical combination lock instead of double bit lock			
60621	Electronic lock with revision instead of double bit lock			
60622	Electronic lock without revision instead of double bit lock			
95050	Locking and blocking barrier			